

| Ordering Information | |
|--|--|
| Model | Description |
| Each Maxxum Module INCLUDES MIS Color Cap and Mounting Hardware All Modules are Single D, except as noted | |
| Media & Coax  | |
| UHD/8K Video | |
| UME8K #908181 | UHD 4K/8K dual jack module, 12Gb/s Signal/Data Serial Interface meets & exceeds SMPTE ST2082-1:2015 <i>Dual D, requires 2 spaces</i> |
|  | |
| DIN 1.0/2.3 Feedthru - DIN C091A Series | |
| UMD12-D12 #908190 | DIN 1.0/2.3 Feedthru, 3GHz, 75 Ohm, AVP DD12, non-recessed, F-F, black plate |
| UMC091A #908605 | Circular DIN, C091A series, 8 Pin female, nickel housing, silver contacts, solder termination |
|  | |
| Phone Jacks, rear solder terminals | |
| UMN3FP6C #907390 | 1/4" Stereo/Mono Locking phone jack, D-size shell, nickel metal housing, silver contacts |
| UMN3FP6C-B #907391 | 1/4" Stereo/Mono Locking phone jack, D-size shell, black metal housing, gold contacts |
| UMN3FP6C-BAG #907307 | 1/4" Stereo/Mono Locking phone jack, D-size shell, black metal housing, silver contacts |
| UMS35J #907302 | 3.5mm Stereo Phone Jack |
| UM35J4G-F #908072 | 3.5mm TRRS 4 Conductor Stereo Phone Jack, feed-thru, with isolated ground |
|  | |
| RCA to RCA Feedthru | |
| UMRCA-R #907297 | RCA Feedthru, red. MIS red cap included |
| UMRCA-W #907298 | RCA Feedthru, white. MIS white cap included |
| UMRCA-Y #907299 | RCA Feedthru, yellow. MIS yellow cap included |
| UMRCA-B #907321 | RCA Feedthru, blue. MIS blue cap included |
| UMRCA-G #907320 | RCA Feedthru, green. MIS green cap included |
| UMRCA-O #907542 | RCA Feedthru, orange. MIS orange cap included |
| UMRCA-K #907543 | RCA Feedthru, black. MIS black cap included |
| Contact AVP if your required connector is not shown | |

| Ordering Information | |
|--|--|
| Model | Description |
| Each Maxxum Module INCLUDES MIS Color Cap and Mounting Hardware All Modules are Single D, except as noted | |
| Data & Network  | |
| Ethernet | |
| UM2RJ45-6AFS #907213 | *Cat6A, RJ45, Feedthru, female to female, Shielded |
| UM2RJ45-6FS #907214 | **Cat6, RJ45, Feedthru, female to female, Shielded |
| UM2RJ45-6AS #907215 | *Cat6A, Shielded, RJ45, Tool-less or 110/Krone Punchdown, 23-26AWG, stranded or solid, h/w |
| UM2RJ45-6S #907216 | **Cat6, Shielded, RJ45, Tool-less or 110/Krone Punchdown, 23-26AWG, stranded or solid, h/w * For Cat3 to Cat6A shielded/unshielded applications ** For Cat3 to Cat6 shielded/unshielded applications |
|  | |
| Neutrik EtherCon | |
| UMNE8FDY-C6 #907387 | Cat6, Panel Connector, IDC, Tool-less, nickel chassis |
| UMNE8FDY-C6-B #907274 | Cat6, Panel Connector, IDC, Tool-less, black chassis |
| UMNE8FDX-Y6 #908590 | CAT6A Panel Connector, shielded, IDC termination, nickel chassis |
| UMNE8FDX-Y6-B #908591 | CAT6A Panel Connector, shielded, IDC termination, black chassis |
| UMNE8FDX-P6 #908180 | CAT6A Panel Connector, shielded, feedthru, nickel chassis |
| UMNE8FDX-P6-B #907990 | CAT6A Panel Connector, shielded, feedthru, black chassis |
|  | |
| RJ11 (RJ12) Feedthru | |
| UMRJ11-F #907218 | RJ11 (RJ12) 6 pos/6 con, Feedthru, female-female |
| RJ11 (RJ12) IDC Tool-less | |
| UMRJ11 #907217 | RJ11 (RJ12) 6 Pos/ 6 Conductor, IDC interface, Toolless |
| *Dual D, requires 2 panel spaces | |

| Ordering Information | |
|---|---|
| Model | Description |
| Each Maxxum Module INCLUDES MIS Color Cap and Mounting Hardware All Modules are Single D, except as noted | |
| Data & Network  | |
| D Sub9 & HD15 | |
| UMD9-FF #907205 | 9-pin D-Sub Female to Female Feedthru |
| UMD9-MM #907206 | 9-pin D-Sub Male to Male Feedthru |
| UMD9-MF #907207 | 9-pin D-Sub Male to Female Feedthru |
| UMD9-FM #907208 | 9-pin D-Sub Female to Male Feedthru |
| UMHD15-FF #907209 | High Density 15-pin D-Sub Female to Female Feedthru |
| UMHD15-MM #907210 | High Density 15-pin D-Sub Male to Male Feedthru |
| UMHD15-MF #907211 | High Density 15-pin D-Sub Male to Female Feedthru |
| UMHD15-FM #907212 | High Density 15-pin D-Sub Female to Male Feedthru |
| UMD25-FF #908182 | 25-pin D-Sub Female to Female Feedthru <i>*Requires 2 panel spaces</i> |
| UMD25-MM #908183 | 25-pin D-Sub Male to Male Feedthru <i>*Requires 2 panel spaces</i> |
| UMD25-MF #908184 | 25-pin D-Sub Male to Female Feedthru <i>*Requires 2 panel spaces</i> |
| UMD25-FM #908185 | 25-pin D-Sub Female to Male Feedthru <i>*Requires 2 panel spaces</i> |
| UMD25-SCF #908186 | 25-pin D-Sub Female, Solder cup contacts are pre-loaded in connector <i>*Requires 2 panel spaces</i> |
| UMD9-CF #907253 | 9-pin D-Sub Female, socket contacts - crimp |
| UMD9-CM #907254 | 9-pin D-Sub Male, pin contacts - crimp |
| UMD9-SCF #907255 | 9-pin D-Sub Female, solder-cup contacts are pre-loaded into connector |
| UMD9-SCM #907256 | 9-pin D-Sub Male, solder-cup contacts are pre-loaded into connector |
| UMD9-SF #907257 | 9-pin D-Sub Female, solder-cup contacts are loose, not pre-loaded into connector |
| UMD9-SM #907258 | 9-pin D-Sub Male, solder-cup contacts are loose, not pre-loaded into connector |
| UMHD15-CF #907263 | High Density 15-pin D-Sub Female, socket contacts - crimp |
| UMHD15-CM #907264 | High Density 15-pin D-Sub Male, pin contacts - crimp |
| UMHD15-SCF #907265 | High Density 15-pin D-Sub Female, solder-cup contacts are pre-loaded into connector |
| UMHD15-SCM #907081 | High Density 15-pin D-Sub Male, solder-cup contacts are pre-loaded into connector |
| UMHD15-SF #907265 | High Density 15-pin D-Sub Female, solder-cup contacts are loose, not pre-loaded into connector |
| UMHD15-SM #907081 | High Density 15-pin D-Sub Male, solder-cup contacts are loose, not pre-loaded into connector |
| Contact AVP if your required connector is not shown | |

| Ordering Information | |
|--|---|
| Model | Description |
| Each Maxxum Module INCLUDES MIS Color Cap and Mounting Hardware All Modules are Single D, except as noted | |
| Audio & Miscellaneous  | |
| SpeakON Chassis Connectors | |
| UMNL2MP #907275 | 2 pole chassis connector, black D-size flange. <i>Does not intermate with the 4-pole cableconnector</i> |
| UMNL4MP #907276 | 4 pole chassis connector, black D-size flange, silver contacts |
| UMNL4MP-UC #907278 | 4 pole, 40A RMS, 50A audio signal, black D-size flange, MIS & hardware |
|  | |
| Midi and Toslink | |
| UMMIDI #907270 | MIDI Isolated Connector, solder type |
| UMMIDI-F #907970 | MIDI Connector, 5 Pin, Feedthru, female-female |
| UMTOS #907311 | Toslink optical audio coupler, Feedthru |
| UMDSD-60SN #907795 | 6 Position Circular DIN Connector Receptacle, Female Sockets, Solder type |
|  | |
| EDAC 3 PIN | |
| UME3R-C #907259 | 3 Pin EDAC Receptacle with crimp pins |
| UME3R-S #907260 | 3 Pin EDAC Receptacle with solder pins |
| *Dual D, requires 2 panel spaces | |

More photos, drawings & specifications are available at www.AVPbroadcast.com